

Daikin NEOFLON ACX-34 PFA Coating Powder, White

Category : Polymer , Thermoplastic , Fluoropolymer , PFA , Polyperfluoroalkoxyethylene, Molded/Extruded

Material Notes:

NEOFLON PFA coating powder is designed for high build coatings having excellent resistance to chemical and corrosive environments. Description: 30-80 micron thickness. Processing Methods: Electrostatic spray coating. Information provided by Daikin Industries.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Daikin-NEOFLON-ACX-34-PFA-Coating-Powder-White.php

Physical Properties	Metric	English	Comments
Bulk Density	0.750 g/cc	0.0271 lb/in ³	
Thickness	30.0 - 80.0 microns	1.18 - 3.15 mil	

Mechanical Properties	Metric	English	Comments
Coefficient of Friction	0.040 - 0.060	0.040 - 0.060	
Taber Abrasion, mg/1000 Cycles	<= 8.000	<= 8.000	Calculated using estimated density, 9.8 N load, cs-10 wheel

Thermal Properties	Metric	English	Comments
Flammability, UL94	V-0	V-0	
Oxygen Index	>= 95 %	>= 95 %	

Electrical Properties	Metric	English	Comments
Dielectric Constant	1.92 - 2.12	1.92 - 2.12	ASTM D150
	@Frequency 1000 Hz	@Frequency 1000 Hz	
Dielectric Constant	1.92 - 2.12	1.92 - 2.12	ASTM D150
	@Frequency 1e+6 Hz	@Frequency 1e+6 Hz	
Dissipation Factor	0.00010 - 0.00021	0.00010 - 0.00021	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China