

## Daikin POLYFLON L-2 PTFE Low Polymer, White Fine Powder

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Fluoropolymer , PTFE

### Material Notes:

White fine powder. Major Uses: Suited especially to applications requiring fine dispersion of particles. Mold lubrication/separation compounding agent for dry lubricants, paints, plastics, rubber, printing inks, etc. and extreme pressure additive for oil and grease. Information provided by Daikin Industries.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Daikin-POLYFLON-L-2-PTFE-Low-Polymer-White-Fine-Powder.php](http://www.lookpolymers.com/polymer_Daikin-POLYFLON-L-2-PTFE-Low-Polymer-White-Fine-Powder.php)

Physical Properties	Metric	English	Comments
Specific Gravity	2.20 g/cc	2.20 g/cc	
Bulk Density	0.370 g/cc	0.0134 lb/in <sup>3</sup>	
Particle Size	>= 5.0 µm	>= 5.0 µm	Average

Thermal Properties	Metric	English	Comments
Flammability, UL94	V-0	V-0	PTFE Component
Oxygen Index	>= 95 %	>= 95 %	PTFE Component

Electrical Properties	Metric	English	Comments
Dielectric Constant	2.1	2.1	PTFE Component; ASTM D150
	@Frequency 1000 Hz	@Frequency 1000 Hz	
Dissipation Factor	2.1	2.1	PTFE Component; ASTM D150
	@Frequency 1e+6 Hz	@Frequency 1e+6 Hz	
Dissipation Factor	0.00010 - 0.00022	0.00010 - 0.00022	PTFE Component

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China