

Denka VINYKON R3102 PVC, R grade for hard extrusion

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

A PVC resin compound offering excellent physical properties and workability. A broad product lineup is available, including hard and soft grades, as well as those for extrusion and injection molding, etc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Denka-VINYKON-R3102-PVC-R-grade-for-hard-extrusion.php

Physical Properties	Metric	English	Comments
Density	1.418 g/cc	0.05123 lb/in ³	JIS-Z-8807

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	46.70 MPa	6773 psi	JIS-K-6740
Elongation at Break	167 %	167 %	JIS-K-6740
Flexural Strength	75.0 MPa	10900 psi	JIS-K-6740
Flexural Modulus	2.83 GPa	410 ksi	JIS-K-6740
Izod Impact, Notched	0.44145 J/cm	0.82702 ft-lb/in	JIS-K-6740
	@Temperature -20.0 °C	@Temperature -4.00 °F	
	0.57879 J/cm	1.0843 ft-lb/in	JIS-K-6740
	@Temperature 0.000 °C	@Temperature 32.0 °F	
	1.295 J/cm	2.426 ft-lb/in	JIS-K-6740
	@Temperature 23.0 °C	@Temperature 73.4 °F	
Penetration	77	77	[°C], penetration temperature; JIS-K-6740

Thermal Properties	Metric	English	Comments
Vicat Softening Point	87.0 °C	189 °F	JIS-K-6740

Descriptive Properties	Value	Comments
Thermostability, min, JIS-K-6723	70	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China