

Dielectric Polymers NT-5900HL Hot Air Leveling Tape (discontinued **)

Category : Polymer , Adhesive , Tape , Thermoset , Polyester , TS , Silicone

Material Notes:

Crosslinked silicone adhesive with polyester film and crepe paper backing. Features: High temperature resistant No adhesive residue even when there is a delay between wave soldering and tape removal Good conformability Applications: For protecting gold finger contacts during wave soldering and hot air leveling of PCBs. Information provided by Dielectric Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-5900HL-Hot-Air-Leveling-Tape-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Thickness	76.2 microns	3.00 mil	Adhesive
	178 microns	7.00 mil	Backing

Mechanical Properties	Metric	English	Comments
Elongation at Break	5.0 %	5.0 %	
Peel Strength	0.2302 kN/m	1.313 pli	Adhesion
	7.54 kN/m	43.0 pli	Tensile

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	250 °C	482 °F	

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China