

## Dielectric Polymers NT-988 High Tack Laminating Adhesive (discontinued \*\*)

Category : Polymer , Adhesive , Thermoset , Acrylic/Cyanoacrylate Adhesive , Silicone

### Material Notes:

Acrylic copolymer adhesive with silicone treated release paper liner. Features: Excellent adhesion to low surface energy substrates Compatible with most printing inks Applications: Mounting a wide variety of substrates where quick adhesion is critical including coarse, uneven materials, low surface energy films and reverse printed materials. Information provided by Dielectric Polymers.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Dielectric-Polymers-NT-988-High-Tack-Laminating-Adhesive-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-988-High-Tack-Laminating-Adhesive-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Thickness	88.9 microns	3.50 mil	Liner
	102 microns	4.00 mil	Adhesive

Mechanical Properties	Metric	English	Comments
Peel Strength	1.14 kN/m	6.50 pli	180° peel, PET/s.s.

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	21.1 °C	70.0 °F	
	107 °C	225 °F	Shear Adhesive Failure (cohesive failure)

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China