

## Dow BETAFOAM™ 87100 MDI & PMDI Isocyanate

Category : Polymer

**Material Notes:**

BETAFOAM™ 87100 is a component used to make low density, all water blown rigid polyurethane foam. Information provided by Dow

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Dow-BETAFOAM-87100-MDI-PMDI-Isocyanate.php](http://www.lookpolymers.com/polymer_Dow-BETAFOAM-87100-MDI-PMDI-Isocyanate.php)

Physical Properties	Metric	English	Comments
Density	1.24 g/cc	0.0448 lb/in <sup>3</sup>	
Solids Content	>= 98.8 %	>= 98.8 %	EPA Method 24, Procedure B (@ 110°C for 1 hr)
Viscosity	165 cP @Temperature 25.0 °C	165 cP @Temperature 77.0 °F	RVT, #1, 10 RPM

Thermal Properties	Metric	English	Comments
Flash Point	>= 149 °C	>= 300 °F	ASTM D92

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China