

## Dow Corning 200® 0.65 CST FLUID

Category : Fluid

**Material Notes:**

Volatile siloxane fluid (hexamethyldisiloxane).Information provided by Dow Corning

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Dow-Corning-200-065-CST-FLUID.php](http://www.lookpolymers.com/polymer_Dow-Corning-200-065-CST-FLUID.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.760 g/cc @Temperature 25.0 °C	0.760 g/cc @Temperature 77.0 °F	
Viscosity Measure	0.65 cSt	0.65 cSt	kinetic/kinematic
Surface Tension	15.9 dynes/cm	15.9 dynes/cm	

Thermal Properties	Metric	English	Comments
Boiling Point	100 °C	212 °F	
Maximum Service Temperature, Air	200 °C	392 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	
Flash Point	-3.00 °C	26.6 °F	closed cup

Optical Properties	Metric	English	Comments
Refractive Index	1.375	1.375	

Descriptive Properties	Value	Comments
Appearance	clear	
Hydrophobic	yes	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China