

Dow Corning MOLYKOTE® G-2001

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

Lithium thickened bearing grease based on synthetic hydrocarbon Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-MOLYKOTE-G-2001.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.00 g/cc @Temperature 25.0 °C	1.00 g/cc @Temperature 77.0 °F	

Mechanical Properties	Metric	English	Comments
Four Ball Extreme Pressure, Weld Load	152.9 kg	337.1 lb (mass)	
Penetration P(60), 1/10 mm	265 - 295	265 - 295	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	130 °C	266 °F	
Minimum Service Temperature, Air	-50.0 °C	-58.0 °F	
Dropping Point	>= 190 °C	>= 374 °F	

Descriptive Properties	Value	Comments
Color	beige	
NLGI Number	2	
Thickening System	lithium-calcium	
Water Resistant	yes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China