

Dow Latex XZ 92240.03 Experimental Latex

Category: Polymer, Thermoplastic, Styrene-Butadiene

Material Notes:

Description: XZ 92240.03 Experimental latex is an aqueous dispersion of a modified carboxylated styrene butadiene copolymer. It has been developed for use as a precoat /adhesive latex for secondary backing of tufted carpet where a medium handle is required. Applications:

Precoating and Secondary backingInformation provided by Styron

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Latex-XZ-9224003-Experimental-Latex.php

Physical Properties	Metric	English	Comments	
Solids Content	50 - 51 %	50 - 51 %		
Particle Mesh Size	100 Mesh	100 Mesh	<0.1 g/l residues	
	325 Mesh	325 Mesh	<0.2 g/l residues	
pH	7.2 - 7.6	7.2 - 7.6		
Brookfield Viscosity	50 - 350 cP	50 - 350 cP	#2 @ 50 rpm	

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	2.00 °C	35.6 °F	

Descriptive Properties	Value	Comments
Minimum film formation temperature	<0°C	
Styrene content in polymer	0.58	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China