

Dow TONE™ 0310 Polyol

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS

Material Notes:

TONE™ 0310 polyol is a very low melting tri-functional liquid polyol for use in polyurethane elastomers, coatings, adhesives and soft foams. Information provided by Dow

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-TONE-0310-Polyol.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.073 g/cc	1.073 g/cc	
Viscosity Measure	270 cSt @Temperature 55.0 °C	270 cSt @Temperature 131 °F	
Molecular Weight	900 g/mol	900 g/mol	
Maximum Moisture Content	0.030	0.030	wt% water

Thermal Properties	Metric	English	Comments
Melting Point	27.0 - 32.0 °C	80.6 - 89.6 °F	

Chemical Properties	Metric	English	Comments
Total Acid Number	<= 0.25	<= 0.25	[mg KOH/g]

Descriptive Properties	Value	Comments
Hydroxyl Number mg KOH/g	187	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China