

Dow TONE™ 305 Polyol

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS

Material Notes:

TONE™ 0305 polyol is a very low equivalent weight tri-functional liquid polyol for use in urethane cast elastomers, coatings, adhesives and soft foams. Information provided by Dow

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-TONE-305-Polyol.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.072 g/cc	1.072 g/cc	
Viscosity Measure	200 cSt @Temperature 55.0 °C	200 cSt @Temperature 131 °F	
Molecular Weight	540 g/mol	540 g/mol	
Maximum Moisture Content	0.030	0.030	wt% water

Thermal Properties	Metric	English	Comments
Melting Point	15.0 - 20.0 °C	59.0 - 68.0 °F	

Chemical Properties	Metric	English	Comments
Total Acid Number	<= 0.25	<= 0.25	[mg KOH/g]

Descriptive Properties	Value	Comments
Hydroxyl Number mg KOH/g	311.7	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China