

DuPont Appeel® LSR11D625 Lidding Sealant Resin (discontinued **)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Appeel® LSR11D625 is a modified ethylene vinyl acetate copolymer resin designed to function as a sealing layer for lidding applications. It is most often suggested to provide strong peelable seals to polypropylene, and moderate seals to polystyrene, polyester, PVC and is available in pellet form for use in conventional extrusion or coextrusion equipment designed to process polyethylene resins. Information provided by DuPont™

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Appeel-LSR11D625-Lidding-Sealant-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.940 g/cc	0.0340 lb/in ³	ASTM D792
Melt Flow	7.2 g/10 min @Load 2.16 kg, Temperature 190 °C	7.2 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	94.0 °C	201 °F	DSC; ASTM D3418
Vicat Softening Point	68.0 °C	154 °F	ASTM D1525

Processing Properties	Metric	English	Comments
Rear Barrel Temperature	140 °C	284 °F	Blow Film
	160 °C	320 °F	Extrusion Coating
Middle Barrel Temperature	150 °C	302 °F	Blow Film
	220 °C	428 °F	Extrusion Coating
Front Barrel Temperature	160 °C	320 °F	Blow Film
	234 °C	453 °F	Extrusion Coating
Adapter Temperature	180 °C	356 °F	Blow Film
	234 °C	453 °F	Extrusion Coating
Die Temperature	180 °C	356 °F	Blow Film
	235 °C	455 °F	Extrusion Coating

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China