

DuPont Elvaloy® 4924 Ethylene/Vinyl Acetate/Carbon Monoxide Copolymer

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Specialized copolymers deliver flexibility, toughness and weatherability to adhesives, plastics, highways and roofing. Availability:

Globally Information provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Elvaloy-4924-EthyleneVinyl-AcetateCarbon-Monoxide-Copolymer.php

Physical Properties	Metric	English	Comments
Density	1.03 g/cc	0.0372 lb/in ³	ASTM D792 - ISO 1183
Melt Flow	7.0 - 23 g/10 min @Load 2.16 kg, Temperature 190 °C	7.0 - 23 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238 - ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	10.90 MPa	1581 psi	ASTM D638 - ISO 527-2
Elongation at Break	736 %	736 %	ASTM D638 - ISO 527-2

Thermal Properties	Metric	English	Comments
Melting Point	70.0 °C	158 °F	ASTM D3418 - ISO 3146
Glass Transition Temp, Tg	-36.0 °C	-32.8 °F	ASTM D3418

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China