

DuPont Elvax® 3136 Ethylene-Vinyl Acetate Copolymer Resin for Blown Film (discontinued **)

Category : Polymer , Film , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate Copolymer (EVA), Film Grade

Material Notes:

12 wt% Vinyl Acetate. General Elvax® information: Elvax® packaging grade resins include low seal temperatures for use in coextrusions or for packaging temperature sensitive materials, excellent drawability for easy processing, good flex-crack resistance for liquid packaging, high toughness, low shrink for water bath applications, and excellent optical properties. It adheres to many materials. It is commonly used as a tie layer in certain coextrusions with dissimilar surfaces. Information provided by DuPont Packaging Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Elvax-3136-Ethylene-Vinyl-Acetate-Copolymer-Resin-for-Blown-Film-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.940 g/cc	0.0340 lb/in ³	ASTM D792
Melt Flow	0.50 g/10 min	0.50 g/10 min	Condition not noted.; ASTM D1238

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China