

DuPont Fusabond® MB265D High Density Polyethylene (discontinued **)

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

Typical Use: CompatibilizerCoupling agent for nonhalogen, flame retarded wire and cable compounds containing fillers such as aluminum trihydrate or magnesium hydroxideNatural fiber wood-plastic compoundsAvailability: North AmericaInformation provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Fusabond-MB265D-High-Density-Polyethylene-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.950 g/cc	0.0343 lb/in ³	
Melt Flow	12.3 g/10 min	12.3 g/10 min	

Thermal Properties	Metric	English	Comments
Melting Point	131 °C	268 °F	

Descriptive Properties	Value	Comments
MAH Graft Level, wt%	High	FTIR (DuPont)

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China