

DuPont Fusabond® MB528D Linear Low Density Polyethylene (discontinued **)

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polyethylene (PE) , LLDPE

Material Notes:

Typical Use: Coupling agent for filled PE systems such as nonhalogen flame retardant filled wire and cable compounds
Adhesion promoter
Availability: North America
Information provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Fusabond-MB528D-Linear-Low-Density-Polyethylene-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc	0.0332 lb/in ³	
Melt Flow	6.8 g/10 min	6.8 g/10 min	

Thermal Properties	Metric	English	Comments
Melting Point	114 °C	237 °F	

Descriptive Properties	Value	Comments
MAH Graft Level, wt%	Very High	FTIR (DuPont)

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China