

## **DuPont Fusabond® MD226D Linear Low Density Polyethylene (discontinued** \*\*)

Category: Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Polyethylene (PE), LLDPE

## **Material Notes:**

Typical Use: CompatibilizerCoupling agent for nonhalogen, flame retarded wire and cable compounds containing fillers such as aluminum trihydrate or magnesium hydroxideNatural fiber wood-plastic compoundsComplies to FDA 21CFR 175.105Availability: North Americalnformation provided by DuPont.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_DuPont-Fusabond-MD226D-Linear-Low-Density-Polyethylene-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.930 g/cc	0.0336 lb/in <sup>3</sup>	
Melt Flow	1.5 g/10 min	1.5 g/10 min	

Thermal Properties	Metric	English	Comments
Melting Point	122 °C	252 °F	

Descriptive Properties	Value	Comments
MAH Graft Level, wt%	High	FTIR (DuPont)

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China