

**DuPont Fusabond® MF416D Ethylene Propylene Rubber (discontinued \*\*)**

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

**Material Notes:**Typical Use: Nylon 6/6 toughener  
Complies to FDA 21CFR 175.105  
Availability: North America  
Information provided by DuPont.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_DuPont-Fusabond-MF416D-Ethylene-Propylene-Rubber-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_DuPont-Fusabond-MF416D-Ethylene-Propylene-Rubber-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Density	0.870 g/cc	0.0314 lb/in <sup>3</sup>	
Melt Flow	23 g/10 min @Load 2.16 kg, Temperature 280 °C	23 g/10 min @Load 4.76 lb, Temperature 536 °F	

Thermal Properties	Metric	English	Comments
Melting Point	29.8 °C	85.6 °F	

Descriptive Properties	Value	Comments
MAH Graft Level, wt%	High	FTIR (DuPont)

**Contact Songhan Plastic Technology Co.,Ltd.**Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China