

DuPont Performance Polymers AquaStik® AQS-2900 Polychloroprene Latex (discontinued **)

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Aquastik™ polychloroprene latexes have been designed for the adhesives industry. They provide an environmentally friendly alternative to solvent-borne systems. This grade features fast break. 59% Solids. Main uses are in adhesives. Initial pH is 12. Sol polymer type. Sodium salts of disproportionated rosin acids used as emulsifying agent. Very fast crystallization rate. Information provided by DuPont Dow Elastomers. This former DuPont Dow Elastomers product line is now produced by DuPont Performance Elastomers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-AquaStik-AQS-2900-Polychloroprene-Latex-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	1.11 g/cc	0.0401 lb/in ³	Latex
	1.23 g/cc	0.0444 lb/in ³	Polymer
Brookfield Viscosity	>= 200 cP	>= 200 cP	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China