

DuPont Performance Polymers Zytel® RS LC2800 NC010 Nylon (Unverified Data**)

Category : Polymer , Thermoplastic , Nylon

Material Notes:

Plasticized Renewably Sourced Polyamide Developed for Extrusion Information provided by DuPont Performance Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Performance-Polymers-Zytel-RS-LC2800-NC010-Nylon-nbspUnverified-Data.php

Mechanical Properties	Metric	English	Comments
Tensile Modulus	0.550 GPa	79.8 ksi	DAM; ISO 527-1/-2
Charpy Impact, Notched	1.60 J/cm ²	7.61 ft-lb/in ²	DAM; ISO 179/1eA

Thermal Properties	Metric	English	Comments
Melting Point	220 °C	428 °F	DAM; 10°C/min; ISO 11357-1/-3
Glass Transition Temp, Tg	30.0 °C	86.0 °F	DAM; 10°C/min; ISO 11357-1/-2

Descriptive Properties	Value	Comments
Additives	Plasticiser	
Delivery Form	Pellets	
Part Marking Code	>PA-P<	ISO 11469
Processing	Coatable	
	Film Extrusion	
	Other Extrusion	
	Profile Extrusion	
	Sheet Extrusion	
Regional Availability	Asia Pacific	
	Europe	
	Global	
	Near East/Africa	
	North America	
	South and Central America	

Resin Identification Descriptive Properties	PA-P Value	ISO 1043 Comments
Special Characteristics	Heat stabilised or stable to heat	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China