

DuPont Teijin Films Melinex® 478 Polyester Film, 200 Gauge

Category : Polymer , Film , Thermoplastic , Polyester, TP , Polyester Film

Material Notes:

Melinex® 478 is a high clarity polyester film manufactured with a coating on both surfaces that improves slip and handling characteristics. Typical Applications: Melinex 478 is used in many general industrial applications where clarity and handling properties are critical, e.g., overlay, lamination and printing applications. Information provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Teijin-Films-Melinex-478-Polyester-Film-200-Gauge.php

Mechanical Properties	Metric	English	Comments
Film Tensile Strength at Yield, MD	>= 89.6 MPa	>= 13000 psi	ASTM D882A
Film Tensile Strength at Yield, TD	>= 89.6 MPa	>= 13000 psi	ASTM D882A
Coefficient of Friction, Dynamic	<= 0.70	<= 0.70	A-B; ASTM D1894
Film Tensile Strength at Break, MD	>= 172 MPa	>= 25000 psi	ASTM D882A
Film Tensile Strength at Break, TD	>= 172 MPa	>= 25000 psi	ASTM D882A

Thermal Properties	Metric	English	Comments
Shrinkage, MD	2.5 % @Temperature 190 °C, Time 300 sec	2.5 % @Temperature 374 °F, Time 0.0833 hour	Unrestrained
Shrinkage, TD	1.0 % @Temperature 190 °C, Time 300 sec	1.0 % @Temperature 374 °F, Time 0.0833 hour	Unrestrained

Optical Properties	Metric	English	Comments
Haze	<= 1.0 %	<= 1.0 %	ASTM D1003

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China