

DuPont Teijin Films Mylar® S1 Polyester Film, 20 Gauge

Category : Polymer , Film , Thermoplastic , Polyester, TP , Polyester Film

Material Notes:

Mylar® S1 films are slightly hazy with surfaces tailored to provide excellent handling and product functionality for a variety of industrial end uses. The outstanding tensile properties and thermal stability typical of Mylar® S1 films are maintained through all gauges offered. General Product Info: Mylar® S1 films have balanced tensile properties with a service range of -94 to 302°F. They are extremely resistant to most chemicals and aging embrittlement. Typical Applications: Decorative metalizing Tape substrates Flexible ducting Book jacket laminations Release sheet Photo substrates Pressure-sensitive tape Thermal reflectors Protective surfacing Carbon-coated ribbon Photo resist Stationery supplies Microforms Information provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Teijin-Films-Mylar-S1-Polyester-Film-20-Gauge.php

Physical Properties	Metric	English	Comments
Density	1.39 g/cc	0.0502 lb/in ³	Typical Mylar®; ASTM D1505

Mechanical Properties	Metric	English	Comments
Film Elongation at Break, MD	110 %	110 %	ASTM D882A
Film Tensile Strength at Break, MD	179 MPa	26000 psi	ASTM D882A

Thermal Properties	Metric	English	Comments
Specific Heat Capacity	1.17 J/g-°C	0.280 BTU/lb-°F	Typical Mylar®
Melting Point	254 °C	489 °F	Typical Mylar® via DSC
Maximum Service Temperature, Air	150 °C	302 °F	
Maximum Service Temperature, Inert	-70.0 °C	-94.0 °F	
Shrinkage, MD	2.1 % @Temperature 150 °C, Time 1800 sec	2.1 % @Temperature 302 °F, Time 0.500 hour	Unrestrained
Shrinkage, TD	1.1 % @Temperature 150 °C, Time 1800 sec	1.1 % @Temperature 302 °F, Time 0.500 hour	Unrestrained

Optical Properties	Metric	English	Comments
Haze	4.5 %	4.5 %	ASTM D1003

Descriptive Properties	Value	Comments
------------------------	-------	----------

Yield (nominal) Descriptive Properties	99185 in ² /lb Value	Comments
---	------------------------------------	----------

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China