

DuPont Teijin Films Teijin® Tetoron® HS Polyester Film, 1400 Gauge

Category : Polymer , Film , Thermoplastic , Polyester, TP , Polyester Film

Material Notes:

Teijin® Tetoron® HS is a very clear polyester film. It is available in a wide range of thicknesses. Typical Applications: OHP Sheet, Labels, ITOLaminated Cards, Window Film. Information provided by DuPont.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Teijin-Films-Teijin-Tetoron-HS-Polyester-Film-1400-Gauge.php

Mechanical Properties	Metric	English	Comments
Film Elongation at Break, MD	210 %	210 %	ASTM D882A
Film Elongation at Break, TD	160 %	160 %	ASTM D882A
Coefficient of Friction, Dynamic	0.35	0.35	ASTM D1894
Coefficient of Friction, Static	0.40	0.40	ASTM D1894
Film Tensile Strength at Break, MD	124.97 MPa	18125 psi	ASTM D882A
Film Tensile Strength at Break, TD	154.96 MPa	22475 psi	ASTM D882A

Thermal Properties	Metric	English	Comments
Shrinkage, MD	0.11 % @Temperature 150 °C, Time 1800 sec	0.11 % @Temperature 302 °F, Time 0.500 hour	Unrestrained
Shrinkage, TD	0.00 % @Temperature 150 °C, Time 1800 sec	0.00 % @Temperature 302 °F, Time 0.500 hour	Unrestrained

Optical Properties	Metric	English	Comments
Haze	11.9 %	11.9 %	ASTM D1003

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China