

E-Polymers EFLEX® S1060 General

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE , Polypropylene (PP)

Material Notes:

S-series (SBS, SEBS compound resins): E-FLEX S series resins are based on SBS/SEBS/SEEPS/PP exhibiting excellent high and low temperature resistance and easy processing with conventional thermoplastic equipment. Overmolding grade is based on SEBS/SEEPS/engineering plastics and exhibit excellent adhesion to engineering plastics as PA, PC, ABS, PC/ABS, PBT. It has product lines for general grade, transparent grade, overmolding grade, high temperature grade, medical grade and extrusion grade. Information Provided by E-Polymers Co., Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_E-Polymers-EFLEX-S1060-General.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.10 g/cc	1.10 g/cc	ASTM D792
Melt Flow	11 g/10 min	11 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60	60	ASTM D2240
Tensile Strength	16.28 MPa	2362 psi	ASTM D412
Elongation at Break	800 %	800 %	ASTM D412
Compression Set	18 %	18 %	ASTM D395
	@Temperature 23.0 °C	@Temperature 73.4 °F	
	42 %	42 %	
	@Temperature 70.0 °C	@Temperature 158 °F	ASTM D395
	70 %	70 %	ASTM D395
	@Temperature 100 °C	@Temperature 212 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China