

E-Polymers EFLEX® S5030 Extrusion

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE , Polypropylene (PP)

Material Notes:

S-series (SBS, SEBS compound resins): E-FLEX S series resins are based on SBS/SEBS/SEEPS/PP exhibiting excellent high and low temperature resistance and easy processing with conventional thermoplastic equipment. Overmolding grade is based on SEBS/SEEPS/engineering plastics and exhibit excellent adhesion to engineering plastics as PA, PC, ABS, PC/ABS, PBT. It has product lines for general grade, transparent grade, overmolding grade, high temperature grade, medical grade and extrusion grade. Information Provided by E-Polymers Co., Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_E-Polymers-EFLEX-S5030-Extrusion.php

Physical Properties	Metric	English	Comments
Melt Flow	0.80 g/10 min @Load 2.16 kg, Temperature 230 °C	0.80 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	35	35	ASTM D2240
Tensile Strength	18.05 MPa	2618 psi	ASTM D412
Elongation at Break	930 %	930 %	ASTM D412
Compression Set	10 % @Temperature 23.0 °C	10 % @Temperature 73.4 °F	ASTM D395
	35 % @Temperature 70.0 °C	35 % @Temperature 158 °F	ASTM D395

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China