

## E-Polymers EFLEX® S5050 Extrusion

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE , Polypropylene (PP)

### Material Notes:

S-series ( SBS, SEBS compound resins): E-FLEX S series resins are based on SBS/SEBS/SEEPS/PP exhibiting excellent high and low temperature resistance and easy processing with conventional thermoplastic equipment. Overmolding grade is based on SEBS/SEEPS/engineering plastics and exhibit excellent adhesion to engineering plastics as PA, PC, ABS, PC/ABS, PBT. It has product lines for general grade, transparent grade, overmolding grade, high temperature grade, medical grade and extrusion grade. Information Provided by E-Polymers Co., Ltd.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_E-Polymers-EFLEX-S5050-Extrusion.php](http://www.lookpolymers.com/polymer_E-Polymers-EFLEX-S5050-Extrusion.php)

Physical Properties	Metric	English	Comments
Melt Flow	0.50 g/10 min	0.50 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	50	50	ASTM D2240
Tensile Strength	13.734 MPa	1992.0 psi	ASTM D412
Elongation at Break	850 %	850 %	ASTM D412
Compression Set	15 %	15 %	ASTM D395
	@Temperature 23.0 °C	@Temperature 73.4 °F	
	45 %	45 %	ASTM D395
	@Temperature 70.0 °C	@Temperature 158 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China