

EMS-Griltech Griltech® D 1365E Copolyester Hotmelt Adhesive (Apparel Interlinings)

Category : Polymer , Adhesive , Thermoplastic , Polyester, TP

Material Notes:

Description: GRILTEX adhesive products, either in pellet or powdered form, are used to coat apparel interlining substrates. Interlining substrates, coated with GRILTEX adhesive products, provides for excellent resistance and dimensional stability of the finished garment. For technical applications, GRILTEX adhesive products are used to optimize the manufacturing process for the production of automotive interior components or parts for other applications. All values were determined on dried pellets. Main Application System: Paste Dot Main Usage: Men's and Children's Wear, Women's Wear, Leisure and Sports Wear Data provided by EMS-Griltech.

Order this product through the following link:

http://www.lookpolymers.com/polymer_EMS-Griltech-Griltech-D-1365E-Copolyester-Hotmelt-Adhesive-Apparel-Interlinings.php

Physical Properties	Metric	English	Comments
Viscosity	450000 cP	450000 cP	2.16 kg load; ISO 1133
	@Temperature 160 °C	@Temperature 320 °F	
Melt Flow	23 g/10 min	23 g/10 min	cm ³ /10 min; ISO 1133
	@Load 2.16 kg, Temperature 160 °C	@Load 4.76 lb, Temperature 320 °F	

Thermal Properties	Metric	English	Comments
Melting Point	98.0 - 107 °C	208 - 225 °F	DSC
Maximum Service Temperature, Air	<= 40.0 °C	<= 104 °F	Laundering Resistance

Processing Properties	Metric	English	Comments
Processing Temperature	120 - 140 °C	248 - 284 °F	Glue Line Temperature

Descriptive Properties	Value	Comments
Dry Cleaning Resistance	Good	
Steam Resistance	Good	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China