

EMS-Griltech Griltech® D 1666A Copolyamide Hotmelt Adhesive (Apparel Interlinings)

Category : Polymer , Adhesive , Thermoplastic , Nylon

Material Notes:

Description: GRILTEX adhesive products, either in pellet or powdered form, are used to coat apparel interlining substrates. Interlining substrates, coated with GRILTEX adhesive products, provides for excellent resistance and dimensional stability of the finished garment. For technical applications, GRILTEX adhesive products are used to optimize the manufacturing process for the production of automotive interior components or parts for other applications. All values were determined on dried pellets. Main Application System: Paste Dot, Powder Dot, Top Dot, Scatter Coating Main Usage: Women's Wear, Leisure and Sports Wear, Leather and Fur Data provided by EMS-Griltech.

Order this product through the following link:

http://www.lookpolymers.com/polymer_EMS-Griltech-Griltech-D-1666A-Copolyamide-Hotmelt-Adhesive-Apparel-Interlinings.php

| Physical Properties | Metric | English | Comments |
|---------------------|---|---|-----------------------------------|
| Viscosity | 120000 cP @Temperature 160 °C | 120000 cP @Temperature 320 °F | 2.16 kg load; ISO 1133 |
| Melt Flow | 90 g/10 min @Load 2.16 kg, Temperature 160 °C | 90 g/10 min @Load 4.76 lb, Temperature 320 °F | cm ³ /10 min; ISO 1133 |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------------|--------------|-----------------------|
| Melting Point | 75.0 - 85.0 °C | 167 - 185 °F | DSC |
| Maximum Service Temperature, Air | <= 40.0 °C | <= 104 °F | Laundering Resistance |

| Processing Properties | Metric | English | Comments |
|------------------------|----------------|---------------|-------------------------------|
| Processing Temperature | 90.0 - 120 °C | 194 - 248 °F | Glue Line Temperature |
| Roll Temperature | 35.0 - 45.0 °C | 95.0 - 113 °F | Temperature of Engraved Rolls |

| Descriptive Properties | Value | Comments |
|-------------------------|-----------|----------|
| Dry Cleaning Resistance | Very Good | |
| Steam Resistance | Good | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China