

## Eagle Brass 762 Nickel Silver 12%, 1/4 Hard

Category: Metal, Nonferrous Metal, Nickel Alloy

## **Material Notes:**

762 is a nickel silver alloy that has excellent strength, stress relaxation resistance, and solderability. Due to it being extremely resistant to corrosion it doesn't tarnish easily and has a long shelf life. Typical uses include springs for relays, condensers, and decorative belt buckles. Information provided by Eagle Brass Company

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Eagle-Brass-762-Nickel-Silver-12-14-Hard.php

Physical Properties	Metric	English	Comments
Density	8.58 g/cc	0.310 lb/in <sup>3</sup>	Annealed

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell 30T	57 - 75	57 - 75	Thickness > 0.020 Inch
Tensile Strength, Ultimate	448 - 558 MPa	65000 - 81000 psi	
Tensile Strength, Yield	241 - 483 MPa	35000 - 70000 psi	0.2% offset
Elongation at Break	20 - 50 %	20 - 50 %	in 2 in.
Tensile Modulus	124 GPa	18000 ksi	

Thermal Properties	Metric	English	Comments
CTE, linear	16.2 μm/m-°C	9.00 μin/in-°F	
	@Temperature 20.0 - 300 °C	@Temperature 68.0 - 572 °F	
Thermal Conductivity	41.5 W/m-K	288 BTU-in/hr-ft <sup>2</sup> -°F	

Component Elements Properties	Metric	English	Comments	
Copper, Cu	59 %	59 %		
Nickel, Ni	12 %	12 %		
Zinc, Zn	29 %	29 %		

Electrical Properties	Metric	English	Comments
Electrical Resistivity	0.0000198 ohm-cm	0.0000198 ohm-cm	Annealed

## **Contact Songhan Plastic Technology Co.,Ltd.**



Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China