Ensinger Tecapeek® XP-90 Compression Molded PEEK Compound, 25% Fiberglass

Category : Polymer , Thermoplastic , Polyketone , Polyetheretherketone (PEEK) , Polyetheretherketone, PEEK, Glass Fiber Filled

Material Notes:

Ensinger Special Polymers offers over twenty different VICTREX® PEEK blends to choose from and has the capability to blend custom compounds for specific applications. Compression molding results in lower amounts of scrap, uniform physical properties and fewer molded-in stresses.TECAPEEK is a high-perfomance engineering thermoplastic. This semi-crystalline material has a balance of high temperature mechanical properties, chemical and steam resistance, superior wear properties and processability which makes it unique.Typical Applications:Bearings and BushingsDown-hole instrumentationWear RingsBall Valve SeatsElectrical ComponentsBack-up and V-RingsPiston Rings and Rider BandsInformation provided by Ensinger Special Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ensinger-Tecapeek-XP-90-Compression-Molded-PEEK-Compound-25-Fiberglass.php

Physical Properties	Metric	English	Comments
Density	1.52 g/cc	0.0549 lb/in ³	ASTM D792
Filler Content	25 %	25 %	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	105	105	ASTM D785
Tensile Strength	104 MPa	15100 psi	ASTM D638
Elongation at Break	2.8 %	2.8 %	ASTM D638
Flexural Strength	148 MPa	21500 psi	ASTM D790
Flexural Modulus	5.86 GPa	850 ksi	ASTM D790

Thermal Properties	Metric	English	Comments	
Melting Point	343 °C	649 °F	DSC	

Descriptive Properties	Value	Comments
Color	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058



Skype : lookpolymers Address : United North Road 215, Fengxian District, Shanghai City, China