

Ensinger Tecapeek® XP-98HT Compression Molded PEEK HT, 30% Carbon Fiber

Category: Polymer, Thermoplastic, Polyketone, Polyetheretherketone (PEEK), Polyetheretherketone, PEEK, Carbon Fiber Filled

Material Notes:

Ensinger Special Polymers offers over twenty different VICTREX® PEEK blends to choose from and has the capability to blend custom compounds for specific applications. Compression molding results in lower amounts of scrap, uniform physical properties and fewer molded-in stresses. TECAPEEK is a high-perfomance engineering thermoplastic. This semi-crystalline material has a balance of high temperature mechanical properties, chemical and steam resistance, superior wear properties and processability which makes it unique. Applications Include: Bearings and Bushings Down-hole instrumentation Wear Rings Ball Valve Seats Electrical Components Back-up and V-Rings Piston Rings and Rider Bands Information provided by Ensinger Special Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ensinger-Tecapeek-XP-98HT-Compression-Molded-PEEK-HT-30-Carbon-Fiber.php

Physical Properties	Metric	English	Comments
Density	1.44 g/cc	0.0520 lb/in ³	ASTM D792
Filler Content	30 %	30 %	
Crystallinity	35 %	35 %	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	90	90	ASTM D2240
Tensile Strength	98.6 MPa	14300 psi	ASTM D638
Elongation at Break	1.0 %	1.0 %	ASTM D638
Flexural Strength	149 MPa	21600 psi	ASTM D790
Flexural Modulus	8.308 GPa	1205 ksi	ASTM D790

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China