

## Ensinger Tecatron® XP-71 Compression Molded PPS Compound, 20% PTFE Filled Natural

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS) with PTFE Filler

### Material Notes:

Ensinger Special Polymers has over twenty different grades of TECATRON PPS available. Custom formulations can be blended to suit specific applications. Compression molding is amenable to short run production and yields products which are homogenous with low process stress. TECATRON PPS is a highly crystalline high-temperature thermoplastic with an excellent balance of cost, temperature resistance, strength, chemical resistance and flame retardance. TECATRON PPS is often used when long-term high-temperature performance and dimensional stability are a must, even in the presence of aggressive chemicals. Applications: Fuel

Injectors Manifolds Pumps Pistons Gears V-Packing Gaskets Bearings Information provided by Ensinger Special Polymers, Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Ensinger-Tecatron-XP-71-Compression-Molded-PPS-Compound-20-PTFE-Filled-Natural.php](http://www.lookpolymers.com/polymer_Ensinger-Tecatron-XP-71-Compression-Molded-PPS-Compound-20-PTFE-Filled-Natural.php)

Physical Properties	Metric	English	Comments
Density	1.51 g/cc	0.0546 lb/in³	ASTM D792
Filler Content	20 %	20 %	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	84	84	ASTM D2240
Tensile Strength	57.9 MPa	8400 psi	ASTM D638
Elongation at Break	1.6 %	1.6 %	ASTM D638
Flexural Strength	71.0 MPa	10300 psi	ASTM D790

Descriptive Properties	Value	Comments
Color	Dark Brown	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China