

ExxonMobil 100 Exxon Sawguide Oil

Category : Fluid , Lubricant

Material Notes:

EXXON SAWGUIDE OIL is specifically formulated to lubricate the thin saw blades of modern gang saws and edgers. The choice of viscosity grade depends on equipment type, lubricant delivery system design and ambient temperatures. Your Exxon representative can assist in selecting the proper viscosity grade. EXXON SAWGUIDE OIL is specially formulated to meet the lubrication requirements of modern gang saws and edgers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-100-Exxon-Sawguide-Oil.php

Physical Properties	Metric	English	Comments
Density	0.882 g/cc	0.0319 lb/in ³	
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Kinematic Viscosity at 40°C (104°F)	100 cSt	100 cSt	
Kinematic Viscosity at 100°C (212°F)	11.8 cSt	11.8 cSt	
ASTM Color	1.0	1.0	ASTM D1500

Mechanical Properties	Metric	English	Comments
Falex Load Test	0.0160 g	0.0000353 lb	Low Load, 600 lb for 2.5 hr

Thermal Properties	Metric	English	Comments
Pour Point	-24.0 °C	-11.2 °F	
Flash Point	219 °C	426 °F	

Component Elements Properties	Metric	English	Comments
H2O	0.0037 %	0.0037 %	

Descriptive Properties	Value	Comments
Rust Prevention, Distilled Water	pass	ASTM D665A
Rust Prevention, Synthetic Sea Water	pass	ASTM D665B

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China