

## ExxonMobil 120 Exxon Aviation Oil EE Series

Category : Fluid , Lubricant

### Material Notes:

Aviation Oil EE is the brand name of a premium quality line of ashless-dispersant piston engine oils. Formulated with select, highly refined base oils together with ashless-dispersant and anti-oxidant additives, Aviation Oil EE is designed to satisfy the requirements of all major engine manufacturers under all climatic conditions. To meet a wide range of requirements, Aviation Oil EE is available as monogrades in four viscosity grades: 65, 80, 100, and 120. Aviation Oil EE oils are designed to meet the requirements of modern aircraft piston engines used in commercial, military and private aircraft. Ashless-dispersant aviation engine oils have attained wide-spread use due to their ability to keep engines cleaner than non-dispersant oils. The four grades of Aviation Oil EE meet the requirements of major engine manufacturers where monograde ashless-dispersant engine oils are recommended. Aviation Oil EE products are U.S. Military approved under SAE J1899, which replaced MIL-L-22851D and are listed in the U.S. Military Qualified Products List QPL-1899. Specific viscosity grades are approved by Pratt and Whitney, Teledyne Continental Motors, and Textron Lycoming and included in their respective Qualified Products Lists. Appropriate viscosity grades are recommended for Curtis-Wright, Franklin, and Rolls-Royce engines. Compatibility: Aviation Oil EE Series is compatible with nondispersant mineral oils as well as with other ashless-dispersant oils that meet the requirements of MIL-L-22851D/SAE J1899. They can be used in high-time engines that have previously used a straight mineral oil. If this is done, however, it is advisable to carry out the oil-screen inspection recommended by the engine manufacturer.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-120-Exxon-Aviation-Oil-EE-Series.php](http://www.lookpolymers.com/polymer_ExxonMobil-120-Exxon-Aviation-Oil-EE-Series.php)

Physical Properties	Metric	English	Comments
Density	0.893 g/cc @Temperature 15.6 °C	0.0323 lb/in <sup>3</sup> @Temperature 60.1 °F	ASTM D4052
API Gravity	26.7 °	26.7 °	
Viscosity Measurement	114	114	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	268 cSt	268 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	24.2 cSt	24.2 cSt	ASTM D445
Ash	0.00 %	0.00 %	SAE J1747

Thermal Properties	Metric	English	Comments
Pour Point	-23.0 °C	-9.40 °F	ASTM D97
Flash Point	267 °C	513 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Acid Number	0.020	0.020	mgKOH/g; ASTM D664

## **Contact Songhan Plastic Technology Co.,Ltd.**

**Website : [www.lookpolymers.com](http://www.lookpolymers.com)**

**Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)**

**Tel : +86 021-51131842**

**Mobile : +86 13061808058**

**Skype : lookpolymers**

**Address : United North Road 215,Fengxian District, Shanghai City,China**