

ExxonMobil 15W-40 Exxon XD-3 Elite

Category: Fluid, Lubricant

Material Notes:

Exxon XD-3 Elite 15W-40 is a synthetic blend heavy duty diesel engine oil that provides the highest level of protection to modern, high performance diesel engines used in severe on and off highway applications. Exxon XD-3 Elite 15W-40 exhibits outstanding low temperature fluidity, high temperature viscosity retention, and piston deposit control. Exxon XD-3 Elite 15W-40 is highly recommended for use in all high performance diesel engines, including modern low emission engines. Naturally aspirated and turbo-charged diesel powered engines; On-highway light and heavy duty trucking including, mixed fleets; Off-highway industries including: mining, construction, quarrying, and agriculture

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-15W-40-Exxon-XD-3-Elite.php

Physical Properties	Metric	English	Comments
Density	0.870 g/cc	0.0314 lb/in³	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measurement	137	137	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	119 cSt	119 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	15.6 cSt	15.6 cSt	ASTM D445
Ash	1.3 %	1.3 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-30.0 °C	-22.0 °F	ASTM D97
Flash Point	228 °C	442 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	12	12	mg KOH/g; ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China