

ExxonMobil 15W-40 Exxon XD-3 Extra

Category: Fluid, Lubricant

Material Notes:

Exxon XD-3 Extra 15W-40 is a premium, heavy duty diesel engine oil that provides outstanding protection to modern, high performance engines used in the toughest on and off highway applications. Exxon XD-3 Extra 15W-40 has the versatility built in to meet the demanding requirements of modern, low emission diesel engines, as well as older models operating on low- or high-sulfur fuels. Exxon XD-3 Extra 15W-40 is recommended for use in a wide range of heavy duty applications and operating environments and meets the API SL specification for gasoline engines used in mixed fleets. On-highway light and heavy duty trucking; Off-highway industries including trucking, construction, quarrying, and agriculture; Mixed fleets

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-15W-40-Exxon-XD-3-Extra.php

Physical Properties	Metric	English	Comments
Density	0.880 g/cc	0.0318 lb/in³	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measurement	135	135	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	118 cSt	118 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	15.3 cSt	15.3 cSt	ASTM D445
Ash	1.3 %	1.3 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-30.0 °C	-22.0 °F	ASTM D97
Flash Point	228 °C	442 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	12	12	mg KOH/g; ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China