

ExxonMobil 15W-40 Exxon XD-3

Category: Fluid, Lubricant

Material Notes:

Exxon XD-3 10W-30 and 15W-40 are premium diesel engine oils formulated to provide excellent protection to modern, high performance diesel engines used in severe on and off-highway applications. These multigrade diesel engine oils are designed using top quality, highly refined base oils and an effective additive system that protects all parts of the engine. Exxon XD-3 is recommended for use in a wide range of heavy-duty applications and operating environments and meets the latest API specifications for gasoline engines used in mixed fleets. Naturally aspirated and turbo-charged equipment powered equipment manufactured; Over the road heavy and light duty diesel trucks; Pickup trucks and sport utility vehicles with diesel or gasoline engines; Off-Highway operations including: construction, mining, quarrying, and agriculture

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-15W-40-Exxon-XD-3.php

Physical Properties	Metric	English	Comments
Density	0.883 g/cc	0.0319 lb/in³	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measurement	138	138	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	113 cSt	113 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	15 cSt	15 cSt	ASTM D445
Ash	1.1 %	1.1 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-33.0 °C	-27.4 °F	ASTM D97
Flash Point	240 °C	464 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	10	10	mg KOH/g; ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China