

## ExxonMobil 20 Exxon XD-3

Category : Fluid , Lubricant

**Material Notes:**

Exxon XD-3 20, 30, 40 and 50 are premium diesel engine oils blended from high quality base oils and a balanced additive system to meet or exceed the lubrication protection requirements of American diesel engine builders. They are specifically formulated using a versatile blend of ashless dispersants, metallic detergents, and inhibitor chemistry to control oxidation, wear, corrosion and rust. Exxon XD-3 Monogrades are especially suited for two-cycle applications. Diesel powered equipment from American manufacturers; On-highway light and heavy-duty trucking; Off-highway industries including: construction, mining, quarrying, and agriculture; Two-cycle applications

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-20-Exxon-XD-3.php](http://www.lookpolymers.com/polymer_ExxonMobil-20-Exxon-XD-3.php)

Physical Properties	Metric	English	Comments
Density	0.890 g/cc @Temperature 15.0 °C	0.0322 lb/in <sup>3</sup> @Temperature 59.0 °F	ASTM D4052
Viscosity Measurement	98	98	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	66 cSt	66 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	8.5 cSt	8.5 cSt	ASTM D445
Ash	0.80 %	0.80 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-30.0 °C	-22.0 °F	ASTM D97
Flash Point	250 °C	482 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	7.3	7.3	mg KOH/g; ASTM D2896

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China