

ExxonMobil 312 Mobilgard 12 Series

Category : Fluid , Lubricant

Material Notes:

Mobilgard 12 Series by ExxonMobil are high performance diesel engine oils developed for use in trunk piston engines operating on low sulphur distillate fuels in marine and industrial applications. They are formulated to have excellent resistance to oxidation and viscosity increase over a long period of service. They have superior water separating properties and provide excellent corrosion protection. Mobilgard 312 and 412 meet API requirements for CF rating. The Mobilgard 12 Series diesel engine oils are intended for use as cylinder and bearing lubricants in marine and industrial diesel engines operating on distillate fuels or light fuel blends. They are particularly effective in small bore, high speed engines in fishing fleets; in new, severe service engines; and in many types of medium speed engines. They may be used as crankcase lubricants in large crosshead type diesel engines operating on high sulphur fuels. Mobilgard 512 is recommended occasionally by some builders as running-in oil for crosshead type engines.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-312-Mobilgard-12-Series.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.896 g/cc	0.896 g/cc	15°C
Viscosity Measurement	100	100	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	108 cSt	108 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	12 cSt	12 cSt	ASTM D445
Ash	2.1 %	2.1 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-9.00 °C	15.8 °F	ASTM D97
Flash Point	266 °C	511 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	15	15	mgKOH/g; ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China