

ExxonMobil 75W-80 Mobilfluid LT

Category : Fluid , Lubricant

Material Notes:

Mobilfluid LT is an extra high performance multipurpose tractor lubricant engineered to meet or exceed tractor transmission, drivetrain, and hydraulic fluid requirements. This product is designed to optimize the performance of agricultural and industrial tractors operating in a wide range of environments and especially in low ambient temperature applications. This next generation product combines select base oils and an advanced additive package to deliver a variety of lubricant performance properties required by various applications. Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs, and hydrostatic drives used in agricultural, contractor, and industrial applications; Recommended for top-up and refill of systems; Suitable for transmission applications requiring Type A (Suffix A), Dexron, and Type F fluids; Recommended for hydraulic and transmission systems where an SAE 10W-20 engine oil is specified; Do not use in passenger car automatic transmissions

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-75W-80-Mobilfluid-LT.php

Physical Properties	Metric	English	Comments
Density	0.875 g/cc @Temperature 15.0 °C	0.0316 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Brookfield Viscosity	20000 cP @Temperature -40.0 °C	20000 cP @Temperature -40.0 °F	
Viscosity Measurement	180	180	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	34 cSt	34 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.2 cSt	7.2 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-45.0 °C	-49.0 °F	ASTM D97
Flash Point	198 °C	388 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China