

## ExxonMobil 80W-140 Mobilube HD

Category : Fluid , Lubricant

**Material Notes:**

Mobilube HD 80W-140 is a heavy-duty gear lubricant formulated from high performance base oils and an advanced additive system. This lubricant is engineered for commercial axles and final drives where extreme pressures and shock loading are expected. It provides excellent performance where API GL-5 service is required. Heavy-duty axles and final drives requiring API GL-5 level performance; On-highway heavy-duty trucks and commercial vehicles; Off-highway industries including: construction, mining, quarrying, and agriculture; Other heavy-duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-80W-140-Mobilube-HD.php](http://www.lookpolymers.com/polymer_ExxonMobil-80W-140-Mobilube-HD.php)

Physical Properties	Metric	English	Comments
Density	0.890 g/cc	0.0322 lb/in <sup>3</sup>	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measurement	133	133	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	260 cSt	260 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	26.6 cSt	26.6 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-33.0 °C	-27.4 °F	ASTM D97
Flash Point	178 °C	352 °F	ASTM D92

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China