

ExxonMobil Achieve™ 6936G2 Polypropylene Homopolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Product Description: An ultra high melt flow rate metallocene based homopolymer resin designed for meltblown nonwoven. Fabrics with superior barrier properties can be produced at reduced process energy demands. **Availability:** Asia Pacific, North America and South America **Features:** Narrow Molecular Weight Distribution **Uses:** Filtration Medium Industrial Applications Medical/Healthcare Applications Meltblown Nonwovens Personal Care **Processing Method:** Fiber (Spinning) Extrusion **Information provided by ExxonMobil**

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Achieve-6936G2-Polypropylene-Homopolymer.php

Physical Properties	Metric	English	Comments
Melt Flow	1550 g/10 min @Load 2.16 kg, Temperature 230 °C	1550 g/10 min @Load 4.76 lb, Temperature 446 °F	ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China