

ExxonMobil Digilyte® 65 EW-214 Coated, White Opaque OPP Facestock

Category : Polymer , Adhesive , Film , Thermoplastic , Polypropylene (PP) , Polypropylene, Film Grade

Material Notes:

White, polypropylene, pressure-sensitive, label facestock designed to be printed on an Indigo® Omnius® One-Shot Color™ press. This film offers strength and opacity. The ElectroInk® receptive coating assures excellent anchorage and improved abrasion resistance with the ElectroInk digital printing inks. The opposite surface is coated to provide excellent pressure-sensitive adhesive adhesion. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Digilyte-65-EW-214-Coated-White-Opaque-OPP-Facestock.php

Physical Properties	Metric	English	Comments
Thickness	66.0 microns	2.60 mil	
Coating Weight	>= 47.7 g/m ²	>= 29.8 lb/ream	520

Mechanical Properties	Metric	English	Comments
Film Elongation at Break, MD	200 %	200 %	510
Film Elongation at Break, TD	50 %	50 %	510
Film Tensile Strength at Break, MD	84.861 MPa	12308 psi	510
Film Tensile Strength at Break, TD	180.33 MPa	26154 psi	510

Thermal Properties	Metric	English	Comments
Shrinkage, MD	5.0 %	5.0 %	at 275°F; 438
Shrinkage, TD	5.0 %	5.0 %	at 275°F; 438

Optical Properties	Metric	English	Comments
Transmission, Visible	18 %	18 %	417

Descriptive Properties	Value	Comments
Gurley Stiffness, MD, mgf	23	
Gurley Stiffness, TD, mgf	40	
Yield, in2/lb	14500	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China