

ExxonMobil ESCOREZ™ 1102RM (Europe) Petroleum Hydrocarbon Resin

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Adhesive

Material Notes:

Aliphatic hydrocarbon resin specifically designed as a binder for thermoplastic road marking formulations. Availability: Africa & Middle East and Europe
Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-ESCOREZ-1102RM-Europe-Petroleum-Hydrocarbon-Resin.php

Physical Properties	Metric	English	Comments
Brookfield Viscosity	1650 cP @Temperature 160 °C	1650 cP @Temperature 320 °F	ETM E-31
Molecular Weight	750 g/mol	750 g/mol	Mn; ETM E-83

Thermal Properties	Metric	English	Comments
Softening Point	97.8 °C	208 °F	ETM E-24
Glass Transition Temp, Tg	44.0 °C	111 °F	ETM E-90

Optical Properties	Metric	English	Comments
Yellow Index	35 %	35 %	Toluene solution with 50% resin in YI.; ETM E-13

Descriptive Properties	Value	Comments
Thermal Color Stability	89 YI	5hr, 347F (175C), ETM E-15
Wax Cloud Point	148°C	(25/25/50), ETM E-10

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China