

## ExxonMobil ESCOREZ™ 1310 LC Petroleum Hydrocarbon Resin

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Adhesive

### Material Notes:

This product is a light colored, premium aliphatic hydrocarbon resin with narrow molecular weight distribution. It is designed to tackify a variety of adhesive polymers including EVA, metallocene polyolefines, APP, APAO, natural rubber, synthetic polyisoprene, polyisobutylene, SIS block copolymers and butyl rubber. Availability: Africa & Middle East, Europe, Central America, North America and South America. Information provided by ExxonMobil Chemical

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-ESCOREZ-1310-LC-Petroleum-Hydrocarbon-Resin.php](http://www.lookpolymers.com/polymer_ExxonMobil-ESCOREZ-1310-LC-Petroleum-Hydrocarbon-Resin.php)

Physical Properties	Metric	English	Comments
Viscosity	750 cP	750 cP	Melt; ETM 22-31
	@Temperature 160 °C	@Temperature 320 °F	
Molecular Weight	1200 g/mol	1200 g/mol	Mn; ETM 300-83
	1900 g/mol	1900 g/mol	Mw; ETM 300-83

Thermal Properties	Metric	English	Comments
Softening Point	93.7 °C	201 °F	ETM 22-24
Glass Transition Temp, Tg	47.0 °C	117 °F	ETM 300-90

Descriptive Properties	Value	Comments
Color-Initial	25 YI	ETM 22-13
Thermal Color Stability	103 YI	5 hr, 175°C, ETM 22-14
Wax Cloud Point	97°C	(20-40/40) ETM 22-10

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China