

ExxonMobil ESCOREZ™ 1315 Petroleum Hydrocarbon Resin

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Adhesive

Material Notes:

Premium aliphatic resin with a high softening point. It is a tackifying resin designed to provide high temperature performance and cohesive strength with a variety of adhesive polymers including metallocene polyolefines, APP, APAO, SIS block copolymers, natural rubber, synthetic polyisoprene, polyisobutylene, and butyl rubber. Availability: Asia Pacific, Central America, North America and South America. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-ESCOREZ-1315-Petroleum-Hydrocarbon-Resin.php

Physical Properties	Metric	English	Comments
Viscosity	1050 cP	1050 cP	Melt; ETM 22-31
	@Temperature 180 °C	@Temperature 356 °F	
Molecular Weight	1300 g/mol	1300 g/mol	Mn; ETM 300-83
	2700 g/mol	2700 g/mol	Mw; ETM 300-83

Thermal Properties	Metric	English	Comments
Softening Point	114.7 °C	238.5 °F	ETM 22-24
Glass Transition Temp, Tg	63.0 °C	145 °F	ETM 300-90

Descriptive Properties	Value	Comments
Color-Initial	4.5 G	ETM 22-13
Thermal Color Stability	12.3 G	5 hr, 175°C, ETM 22-14
Wax Cloud Point	110°C	ETM 22-10

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China