

ExxonMobil ESCOREZ™ 5600 Petroleum Hydrocarbon Resin

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Adhesive

Material Notes:

Light colored aromatic modified, cycloaliphatic hydrocarbon resin. Designed to tackify a variety of adhesive polymers including EVA, SIS and SEBS block copolymers and metallocene polyolefines. Availability: Africa & Middle East, Europe, Asia Pacific, Central America, North America and South America
Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-ESCOREZ-5600-Petroleum-Hydrocarbon-Resin.php

Physical Properties	Metric	English	Comments
Viscosity	850 cP	850 cP	Melt; ETM 22-31
	@Temperature 160 °C	@Temperature 320 °F	
Molecular Weight	500 g/mol	500 g/mol	Mn; ETM 300-83
	800 g/mol	800 g/mol	Mw; ETM 300-83

Thermal Properties	Metric	English	Comments
Softening Point	102.5 °C	216.5 °F	ETM 22-24
Glass Transition Temp, Tg	52.0 °C	126 °F	ETM 300-90

Descriptive Properties	Value	Comments
Aromaticity	9.8%	ETM 22-50
Color - Initial	1.0 YI	ETM 22-13
Thermal Color Stability	33.1 YI	5 hr, 175°C, ETM 22-14

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China