

ExxonMobil Escorene® AD2528 Adhesive Application Resin

Category : Polymer , Adhesive , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate Copolymer (EVA), Adhesive/Sealant Grade

Material Notes:

Escorene Ultra AD 2528 is a very high flow rate, 27.6% Vinyl Acetate, copolymer, which is useful in formulating hot melt

adhesives. Availability: Latin America, North America and South America Additive: Antiblock: NoSlip: NoThermal Stabilizer: Yes

Applications: Adhesives and Sealants Industrial Sealants Viscosity Modifier Hot Melt Adhesives Wax Blends Packaging Adhesives Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-AD2528-Adhesive-Application-Resin.php

Physical Properties	Metric	English	Comments
Density	0.953 g/cc	0.0344 lb/in ³	ExxonMobil Method
Viscosity	2800 cP @Temperature 190 °C	2800 cP @Temperature 374 °F	ASTM D3236
Vinyl Acetate Content	27.6 %	27.6 %	ExxonMobil Method

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	68	68	15s; ASTM D2240
Hardness, Shore D	15	15	15s; ASTM D2240
Tensile Strength at Break	2.00 MPa	290 psi	ASTM D638
Elongation at Break	240 %	240 %	ASTM D638
Flexural Modulus	0.0276 GPa	4.00 ksi	1% secant; ASTM D790

Thermal Properties	Metric	English	Comments
Melting Point	73.9 °C	165 °F	Peak Melting Temperature; ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China