

ExxonMobil Escorene™ MV 02528EH2 Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 02528EH2 is a copolymer of ethylene and vinyl acetate. Availability: Asia Pacific and Europe Additive: Antiblock: No Slip: No Thermal Stabilizer: Yes Free Flowing Agent: Yes Applications: Hot Melt Adhesives Viscosity Modifier Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-MV-02528EH2-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.942 g/cc	0.0340 lb/in ³	ExxonMobil method
Viscosity	3100 cP @Temperature 190 °C	3100 cP @Temperature 374 °F	Melt
Vinyl Acetate Content	27.5 %	27.5 %	ExxonMobil method

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	1.52 MPa	220 psi	(20 in/min), Molded Properties; ASTM D638
Elongation at Break	140 %	140 %	(20 in/min), Molded Properties; ASTM D638
Tensile Modulus	0.00827 GPa	1.20 ksi	(0.2 in/min), Molded Properties; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	<= 145 °C	<= 293 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China