

ExxonMobil Escorene™ UL 00328 Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 00328 is a copolymer of ethylene and vinyl acetate. Availability: Africa & Middle East and Europe Additive: Antiblock: NoSlip: No Thermal Stabilizer: No Applications: CompoundingFabric CoatingHot Melt AdhesivesInjection MoldingProfile ExtrusionSheet ExtrusionTube ExtrusionWire and Cable Compounds Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-00328-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.951 g/cc	0.0344 lb/in ³	ExxonMobil method
Vinyl Acetate Content	27 %	27 %	ExxonMobil method
Melt Flow	3.0 g/10 min	3.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 0.689 MPa	>= 100 psi	Molded Properties; ISO 527-2/1A
Tensile Modulus	0.0159 GPa	2.30 ksi	Molded Properties; ISO 527-2

Thermal Properties	Metric	English	Comments
Melting Point	<= 160 °C	<= 320 °F	Peak Melting Point; ExxonMobil method
Vicat Softening Point	44.4 °C	112 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China